Qingyuan IBoss Smart Technology Co., Ltd.

iBOSS 1.75mm PETG Filament Orange 3D Printing Filament Toughness Enhanced 3D Printer 1KG

Basic Information

Place of Origin: Qingyuan,china

Brand Name: iBOSS
Certification: ROSH
Model Number: PETG
Minimum Order Quantity: 48kg/rolls
Price: us\$5.5

• Packaging Details: 1KG/PCS, packed into a 30*35CM PU

vacuum shrink bag, 12 corrugated aircraft

CTNs(21.5*20.5*6.9CM) in a 43.1*23.2*43CM box,

• Delivery Time: 5-7days

• Payment Terms: L/C,D/A,D/P,T/T,

• Supply Ability: 10000kg




Product Specification

HS Code: 3916909000
Feature: High Strength
Diameter: 1.75mm
Netweigt: 1kg
Suitable For: Universal
Material: PETG
Weight: 1kg

SUITABLE FOR ALL 3D PRINTERS ON THE MARKET

More Images



Product Description


iBOSS 1.75mm PETG Filament Orange 3D Printing Filament Toughness Enhanced 3D Printer 1KG

The iBOSS 1.75mm PETG Filament in Orange is a top - tier 3D printing material. With a weight of 1KG, it's perfect for various projects. This filament combines the best of PLA and ABS. It's highly tough, which significantly reduces the risk of cracking and warping during 3D printing.

Featuring a diameter of 1.75mm with a tolerance of ±0.02mm, it ensures consistent and smooth extrusion. The recommended print temperature ranges from 220 - 250°C, while the heat bed should be set at 75 - 80°C. This PETG filament is not only durable but also eco - friendly and odorless. Whether you're a hobbyist or a professional, it enables you to create high - quality, detailed 3D prints with excellent surface finish and dimensional accuracy.

Accurate 3D Printer Filament Diameter

Ensuring smooth and uniform extrusion for superior prints.



APPLICATION

Work for 99% FDM 3D Printer & 3D Pen



SUITABLE FOR ALL 3D PRINTERS ON THE MARKET



Model PETG

Net Weight (KG) 1KG

Gross weight 1.4KG

Packing box size 200×200×64mm

Color Orange 1.75mm Diameter(mm) Tolerance(mm) ±0.02mm **Print Temperature** 200-230°C (ºC) Base plat 60°C Temperature (°C) 1.23±0.05g/cm3 Density **Printing Speed** 40-100m Melt Index 14-18g/10min (190°C,2.16kg) Bubble 100% without bubble Length of Line (Ø 1.75mm=330m 1.75±0.2mm) Tensile strength ≥62Mpa Flexural modulus 1970 Mpa **Izod Notch Impact** 7KJ/m2 Strength **Elongation at Break** 52 or 53 (°C, 0.45Mpa) Hydroscopicity 0.005 Reel Size Ø20.0cm * 6.4cm H

About us





1. High quality

Using high quality material and establishing a strict quality control system, assigning specific persons in charge of each part of production, from raw material purchase to assembly.

2. Professional R&D center

Employed designers with 15 years working experience in sanitary industry. Each month will release a new series of products. OEM and ODM are warmly welcomed.

3. Fast dispatch

Most of the products are in stock. Quality below 100pcs can be delivered within 15 days.

4.Small order accepted

Low MOQ accepted. 1pcs are available.

Certifications



iBOSS Qingyuan IBoss Smart Technology Co., Ltd.



0086 15116273361



manager2@iboss3d-export.com



iboss3d-export.com

2nd Floor,Decheng Technology Park,No.42 Shilong Road, Shijiao Town, Qingcheng District,Qingyuan,Guangdong Province,China